COURT OF LAND REGISTRATION

TERRITORY OF HAWAII.

Map and Description with Petition No 188
Petitioner: OAHU COUNTRY CLUB
Valley of Waolani, situated on the northwest side of Nuuanu Valley,
Honolulu, Oahu, being Grant 168 to T.C.B. Rooke.

Beginning at Pohaku Aumiumi, at an old mark arrow (←) on solid rock, which bears by true azimuth from Government Triangulation Stations,

WYLLIE	247° 47' 50"	distant	4977.8 feet;
ROSEBANK	194° 11' 20"	"	4198.4 " ;

and running by true azimuths:-

1. 20° 51' 00" 399.6 feet, along Grant 72 to R.C. Wyllie, to angle in stone wall;
2. 38° 46' 00" 184.9 " , " Stonewall, Grant 72 R.C. Wyllie;
3. 51° 11' 30" 107.5 " , " " " , " " " " " ;
4. 39° 54' 30" 195.2 " , " " " , " " " " " , to point at junction of Streams;
5. 59° 00' 00" 154.0 " , across small stream to point on North side of stream, this course being along Grant 72 R.C. Wyllie;
6. 65° 14' 00" 194.3 " , along Grant 72 R.C. Wyllie, along North bank of stream, to corner of fence, at the north corner of L.C.A. 251, T. Cummins;
7. 55° 30' 00" 194.0 " , along North bank of stream; along L.C.A. 251;
8. 24° 47' 00" 392.7 " , " " " " " ; " " " ;
9. 79° 50' 30" 264.0 " , " " " " " ; along " to " corner of fence;
10. 45° 30' 00" 115.5 " , " fence, along North bank of stream along L.C.A. 251; to the west corner of L.C.A. 251. Thos. Cummins;
11. 64° 19' 30" 165.7 " , " North bank of Stream, to a rock marked +, at end of stonewall; said rock marked +, being by co-ordinate reference from Wyllie Triangulation Station 320.28 feet North and 3017.05 feet East;
12. 168° 16' 30" 325.2 " , " stonewall, along Kalihi Taro & Land Co. Ltd. property;
13. 160° 15' 00" 153.0 " , " " , along Property of the Western & Hawaiian Investment Co. Ltd, to East side of Liliha Street extension;
14. 52° 00' 00" 85.5 " , along Property of Western & Hawaiian Investment Co. Ltd, and East side of Liliha Street extension;
15. 142° 00' 00" 116.7 " , across mauka end of Liliha Street, along north side of Felix Street to point on stone wall;
16. 165° 33' 00" 31.5 " , along stonewall, along Felix Street, to large rock in stonewall, marked + ;
17. 133° 14' 30" 129.4 " , along stonewall, along Felix Street, to stone in line of old stonewall marked + ;
18. 138° 31' 00" 62.1 " , along line of old stonewall, along Felix Street to rock marked Δ;
19. 151° 26' 00" 88.4 " , " " " " " , " " " to stone marked +, from which stone marked + Wyllie Trig. Sta. bears azimuth 67°30' and Rosebank Trig. Sta. bears azimuth 342° 50' 30";
20. 165° 59' 00" 255.0 feet, along line of old stonewall, along Felix Street, crossing mauka end of Rooke Street, and along Gov't. Quarry lot, to stone marked Δ at foot of Pali;
21. 138° 18' 30" 907.5 feet, along Government Quarry Lot, up pali, to a galvanized iron pipe, near a large square rock, on Alewa ridge, at the top edge of the pali, or brow of the Valley; which pipe bears, by true azimuth from Wyllie 223° 48' 30" 2757.8 feet, Rosebank 158° 12' 50" 4500.9 " ;
22. 203° 20' 00" 154.0 feet, along Alewa Government Land, following the top of the pali, or brow of the Waolani Valley;
23. 169° 30' 00" 128.0 feet, along same ;
24. 146° 05' 00" 112.0 " , " " ;
25. 206° 15' 00" 176.0 " , " " ;
26. 192° 01' 00" 468.5 " , " " ;
27. 189° 42' 00" 388.0 " , " " ; to a galvanized pipe, on the edge of the pali and on line of Kapalama Fence; from which galvanized pipe Pohaku Aumiumi bears by true azimuth 300°35' and is distant 2884.9 feet;
28. 219° 00' 00" 588.0 feet, along Kapalama B.P. Bishop Est. land, following the top of the pali or brow of Waolani Valley;
29. 247° 04' 00" 462.5 " " —same— ;
30. 194° 30' 00" 127.0 " , " " , to iron pipe on Knoll, at beginning of sharp well defined ridge running mauka; from this pipe Pohaku Aumiumi bears by true azimuth 323° 22' 30" distant 2775.9 feet; and Galvanized pipe at end of Course No 21, above Gov't. Quarry on Alewa ridge is true azimuth 26°13'30" distant 2361.9 feet;
31. Thence following along the top of the sharp well defined ridge, dividing this land from Kapalama, B.P. Bishop Est. land, to a concrete post on Waolani Knoll, the direct azimuth and distant being 240°19'50" 1724.6 feet;
32. Thence following along the top of the sharp well defined ridge dividing this land from Kapalama B.P. Bishop Est. land to a galvanized pipe, the direct azimuth and distant being 235°05' 1478.5 feet;
33. Thence following along the top of the sharp well defined ridge dividing this land from Kapalama B.P. Bishop Est. land, to a galvanized pipe, set on the mauka brow of the hill called Napuumaia, at head of Waolani Valley, the direct azimuth and distant being 226° 05' 3073.3 feet. From galvanized pipe on Napuumaia, Galvanized Pipe at end of Course 21, above Gov't. Quarry on Alewa Ridge bears by true azimuth 52°7' distant 8428 feet, and the following Triangulation Stations bear by true azimuths:- Puowaina 23°11', Puu Ohia 330° 50' 30", Rosebank 22° 59 ;
34. 296° 24' 00" 168.0 feet, down along small spur ridge, at head of Waolani Valley, along Government land ;
35. 343° 05' 198.0 " , along same ;
36. 315° 20' 150.0 " , " " ;
37. 22° 43' 745.0 " , " top of sharp well defined ridge called Kakaalele to galvanized iron pipe, along Gov't. land;
38. Thence along the top of the sharp well defined ridge, called Kekaalele, along Gov't. land, to a galvanized pipe, the direct azimuth and distant being 20°15'30" 724.5 feet;
39. Thence along the top of the sharp well defined ridge, following along the gap or saddle along Gov't. land and the Nuuanu Homestead Lots, to a large rock on the summit of Kahalepahu ridge, the direct azimuth and distant being 31°35'30" 1447 feet;
40. Thence along the top of the sharp well defined ridge, along Nuuanu Homestead Lots, and Gov't. land to a galvanized pipe on round hillock called Kapoholua, the direct azimuth and distant being 29°23' 1241.8 feet;
41. Thence following along the top of the sharp well defined ridge, to fence at foot of steep rocky part of spur, this course along Government Lot, the direct azimuth and distant being 51°19' 1509.7 feet;
42. 44° 20' 00" 103.0 feet, along fence on top of ridge, along Government Lot;
43. 34° 50' 00" 163.0 " , " " " " " " " " ;
44. 52° 31' 00" 117.8 " , " " , along Government Lot ;
45. 30° 21' 00" 38.0 " , " " and stonewall along Government Lot ;
46. 17° 02' 00" 406.7 " , " stonewall, along Government Lot to stone at foot of corner of stonewalls marked + ;
47. 15° 34' 30" 376.3 feet, along Government Lot, to the point of beginning.

Containing an Area of 378 Acres

Honolulu
July 12th 1910

E. D. Baldwin
Surveyor.

Baldwin & Alexander
Civil Engineers & Surveyors
405 Judd Bldg.

Court of Land Registration
Filed
Sept 30-1910
10 min 10 A.M.
M. T. Simonton.
Registrar

The above plan and description has been duly examined by me and found correct.
Geo. F. Wright
Asst. Engr. & Surveyor
Land Reg Court. Oct 5-1910.

I hereby certify that this is a true and correct copy of Petition 188
Geo. F. Wright
Nov. 17-1910.